



Mi-Glow[®] 800L

Physical Characteristics

Forest green liquid, odorless.

Particle Certification

Particles, carrier and mixture meet or exceed all applicable industry specifications, including but not limited to ASTM E-1444, MIL-STD-271, ASTM E 709, ASME B & PV Code - Section V and NAVSEA 250-1500-1, AMS 3045, AMS 3161, AMS 2641 and A-A-59230. Certification is included with each shipment.

Mi-Glow[®] 800L is a preproportioned combination of Mi-Glow[®] 800 fluorescent yellow-green particles and CircleSol M[™], a refined petroleum distillate, packaged ready-for-use in five gallon cans. It is designed to be used with UV-A light to detect very fine discontinuities in finished products.

Particle Color

Fluorescent yellow-green

Average Particle Size 3 µm

AMS Standard 3045

SAE Sensitivity*

8

[*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

Temperature Range

32-120°F (0-49°C)

Related Product Information:

Safety Data Sheet Technical Bulletin 272

Item # FG-3143 Package Size 5 gallons/pail



www.circlesafe.com P.O. Box 1228, Hinckley, Illinois 60520 ph 815.286.3271 | fax 815.286.3352 email customerservice@circlesafe.com