

Mi-Glow<sup>®</sup> 800 fluorescent yellowgreen particles premixed with powdered Wetting Agent 34 for use in water media. It is designed to be used with UV-A light to detect very fine discontinuities in finished products. Wetting Agent 34 is low foaming and has excellent wetting characteristics.

# Mi-Glow<sup>®</sup>

# Mi-Glow<sup>®</sup> 834

## **Physical Characteristics**

Forest green powder with a slight detergent odor.

#### Particle Certification

Particles meet or exceed all relevant industry specifications, including but not limited to ASTM E 1444, AMS 3044, MIL-STD-271, NAVSEA 250-1500-1, and NTR-1E. Certification is included with each shipment.

## Particle Color

Fluorescent Yellow-Green

## Average Particle Size

3 µm

# AMS Standard

3044

## SAE Sensitivity\*

8

[\*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.1

#### **Temperature Range**

32-120°F (0-49°C)

## **Related Product Information:**

Safety Data Sheet Technical Bulletin 204

ltem # FG-3125 FG-3126 30 pounds/pail





www.circlesafe.com P.O. Box 1228, Hinckley, Illinois 60520 ph 815.286.3271 | fax 815.286.3352 email customerservice@circlesafe.com