

Mi-Glow<sup>®</sup> 920 is fluorescent yellow-green particles used with CircleSol M<sup>™</sup>, a refined petroleum distillate. It is designed to be used with UV-A light to detect forging type discontinuities. It meets or exceeds AMS 3044 and all applicable industry specifications.

# **Mi-Glow**<sup>®</sup>

### Mi-Glow<sup>®</sup> 920

#### **Physical Characteristics**

Green powder, odorless.

#### **Particle Certification**

Particles meet or exceed all relevant industry specifications, including but not limited to ASTM E 1444, AMS 3044, MIL-STD-271, NAVSEA 250-1500-1, NTR-1E. Certification is included with each shipment.

#### Particle Color

Fluorescent Yellow-Green

## Average Particle Size

.

AMS Standard 3044

#### SAE Sensitivity\*

8

[\*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

#### **Temperature Range**

32-120°F (0-49°C)

#### **Related Product Information:**

Safety Data Sheet Technical Bulletin 213

**Item #** FG-3162 Package Size 2 pounds/jar



www.circlesafe.com P.O. Box 1228, Hinckley, Illinois 60520 ph 815.286.3271 | fax 815.286.3352 email customerservice@circlesafe.com