



**Circle Systems, Inc.**

1210 Osborne Road  
St Marys Georgia 31558  
Ph. 815-286-3271  
Fax: 815-286-3352  
customerservice@circlesafe.com

---

## **Technical Bulletin 189 Wetting Agent 34**

Wetting Agent 34 is a powdered wetting agent for use with Mi-Glow® fluorescent particles, using thorough mixing procedures. Wetting Agent 34 has good defoaming characteristics and good wetting properties.

### **Properties**

Color: White

Specific Gravity: .7 g/ml

pH: 8.5

Recommended Concentration: The recommended concentration is 5.3 oz./10-gallons (4.0 grams/liter).

Temperature Limit: 120°F Maximum

Shelf Life: Four (4) years when closed containers are stored in a clean, dry environment, away from excessive heat and cold. A Certificate of Shelf Life is available upon request.

### **Directions for Use**

Preparation: For best results, add a small amount of water to the mixture to form a slurry prior to addition to the bath.

System Conversion: When changing a bath from a refined petroleum distillate system, reference Technical Bulletin 244.

---

DISCLAIMER: OUR TECHNICAL ADVICE, INFORMATION AND STATEMENTS GIVEN VERBALLY, IN WRITING OR IN THE FORM OF TEST RESULTS, ARE OFFERED FOR YOUR GUIDANCE WITHOUT WARRANTY. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. IT IS THE USER'S RESPONSIBILITY TO TEST THE SUITABILITY OF EACH PRODUCT FOR HIS INTENDED PROCESS AND APPLICATIONS. OUR GUARANTEE IS LIMITED TO THE CONSISTENT QUALITY OF OUR PRODUCTS.

---